



Application Data Sheet for: FRACING Density Gauge

BERTHOLD TECHNOLOGIES USA, LLC
 99 Midway Lane Oak Ridge, TN 37830
 PHONE (865) 483-1488
 FAX (865) 425-4309

Customer Information

Company Name	<input type="text"/>	Phone Number	<input type="text"/>
Contact Name	<input type="text"/>	Fax Number	<input type="text"/>
Street or P.O. Box	<input type="text"/>		
City	<input type="text"/>	Email Address	<input type="text"/>
State /Province	<input type="text"/>		
Zip Code	<input type="text"/>		
Country	<input type="text"/>		
Project Name <input type="text"/>		Date <input type="text"/>	

Process Specifications

Slurries -	MIN	Units	MAX	Units
Carrier density	<input type="text"/>		<input type="text"/>	
Solids density	<input type="text"/>		<input type="text"/>	
Calibrated Density Range -	MIN	Units	MAX	Units
	<input type="text"/>		<input type="text"/>	
Pipe Pressure -	MIN		MAX	
	<input type="text"/>	psi	<input type="text"/>	psi

Outputs

Number of 4-20 mA outputs per gauge required- <input type="text"/>				
			MIN	MAX
Units	(g/cc3, PPG, Kg/m3)	<input type="text"/>	<input type="text"/>	<input type="text"/>
Units	PPA, KgSA, etc)	<input type="text"/>	<input type="text"/>	<input type="text"/>
		Range		
		Range		

Physical Arrangement

Nominal pipe diameter	<input type="text"/>	inches	
Schedule	<input type="text"/>		
Inside diameter	<input type="text"/>	mm or in	
Outside diameter	<input type="text"/>	mm or in	
1st wall thickness	<input type="text"/>	mm or in	Material <input type="text"/>
2nd wall thickness	<input type="text"/>	mm or in	Material <input type="text"/>
Insulation thickness	<input type="text"/>	mm or in	Material <input type="text"/>
Liner thickness	<input type="text"/>	mm or in	Material <input type="text"/>

Retrofit Using Existing Source & Shield

Original Source Date	<input type="text"/>	
Original Source Size	<input type="text"/>	mCi
Type of Isotope	<input type="text"/>	
Supplier of Source	<input type="text"/>	